

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 102 349 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

23.05.2001 Bulletin 2001/21

(51) Int Cl.7: **H01Q 19/10**, H01Q 9/28,
H01Q 1/42, H01Q 1/24

(21) Application number: **00124374.0**

(22) Date of filing: **20.11.2000**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: **22.11.1999 US 447166**

(71) Applicant: **TRW Inc.**

Redondo Beach, California 90278 (US)

(72) Inventors:

- **Jennetti, Anthony G.**
Sunnyvale, CA 94086 (US)
- **Serrano, Francisco J.**
Los Gatos, CA 95032 (US)

• **Manassero, Greg A.**

San Jose, CA 95129 (US)

• **Belingeri, Ralph A.**

Woodside, CA 94062 (US)

• **Rucker, Donald L.**

Santa Cruz, CA 95060 (US)

• **Humphrey, Brent R.**

San Jose, CA 95139 (US)

(74) Representative: **Schmidt, Steffen J., Dipl.-Ing.**
Wuesthoff & Wuesthoff,
Patent- und Rechtsanwälte,
Schweigerstrasse 2
81541 München (DE)

(54) **High performance, directional cellular band antenna**

(57) An indoor cellular band antenna (10) that is low cost, easy to assemble, easy to manufacture, and has better performance than those antennas existing in the art. The antenna (10) has an outer metal housing (12) including angled side panels (22, 24), trapezoidal-shaped top and bottom panels (18, 20) and a rectangular shaped back panel (26) defining a 90° truncated corner configuration. A radome (14) is positioned over the front of the housing (12) by sliding it beneath extending clips (30) formed to the side panels (22, 24). An antenna dipole (16) is mounted in the housing (12) and includes two dipole members (42, 44). Each dipole member (42, 44) includes a rectangular dipole element (46, 58), extended transmission balun members (52, 59) and a back

mounting plate (54, 61) formed from a single piece of metal. The transmission balun members (52, 59) are parallel to each other and specially spaced to provide a predetermined and electromagnetic coupling between the dipole members (42, 44). An antenna cable (36) extends through the top panel (18) of the housing (12). An outer conductor (62) of the cable (36) is electrically connected to one of the transmission balun member (52) of one dipole member (42) and an inner conductor (60) is electrically connected to the dipole element (46) of the same dipole member (42). The inner and outer conductors (60, 62) of the cable (36) are mounted to the dipole member (42) by connectors (64, 70) formed from the dipole member (42).

EP 1 102 349 A2

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This invention relates generally to an antenna and, more particularly, to an indoor, low cost, high performance, directional cellular band antenna employing a 90E truncated reflector housing and rectangular dipole elements.

2. Discussion of the Related Art

[0002] Many types of communications antennas exist in the art. Each various antenna design must provide suitable performance at the particular bandwidths of operation. For cellular telephones, the antenna must effectively receive and transmit signals in the 800-1050MHz range. Certain building materials may significantly attenuate cellular band signals, thus reducing the ability of the telephone to operate effectively indoors. Therefore, it may be desirable to provide a cellular band antenna within a room or interior space that it electrically connected to an exterior antenna to provide suitable operation of the cellular telephones within the space. Several different requirements drive the design of these types of antennas. These requirements include low cost, ease of manufacture and assembly, ease of installation, ability to be inconspicuously mounted in the space, high performance over the desired bandwidths, suitable front-to-back ratio (FBR), and reliability.

[0003] State of the art antennas of this type include triangular dipoles, 90E corner reflector antennas, and radome antennas such as the Allen MicroFill indoor antennas, Model Nos. DB781 and DB791, and the Suhner planar antennas, known to those skilled in the art. However, improvements can be made in the existing antenna art to provide an increase in one or more of the above-described desirable features. It is therefore an object of the present invention to provide an indoor antenna operable in the cellular band frequency range that includes significant improvements over the state of the art antenna designs.

SUMMARY OF THE INVENTION

[0004] In accordance with the teachings of the present invention, an indoor cellular band antenna is disclosed that is low cost, easy to manufacture and assemble, easy to install, and has better performance than the comparable antennas existing in the art. The antenna has an outer metal housing including angled side panels, trapezoidal-shaped top and bottom panels and a rectangular-shaped back panel defining a 90E truncated corner configuration. A radome is positioned over the front of the housing by sliding it beneath extended clips formed to the side panels. An antenna dipole is

mounted in the housing and includes two dipole members positioned to be substantial mirror images of each other except for minor differences. Each dipole member includes a rectangular dipole element, an extended transmission balun member, and a back mounting plate. The transmission balun members are parallel to each other and are spaced apart a predetermined distance to provide electromagnetic coupling between the dipole members. An antenna cable extends through the top panel of the housing to be connected through a distribution system to an exterior antenna. An outer conductor of the cable is electrically connected to the transmission balun member of one of the dipole members and an inner conductor is electrically connected to the dipole element of the same dipole member. The inner and outer conductors of the cable are mounted to the dipole portion by connectors formed from the dipole member. Additional objectives, advantages, and features of the present invention will become apparent from the following description and appended claims, taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005]

Figure 1 is a perspective view of an indoor, cellular band antenna, according to an embodiment of the present invention;

Figure 2 is a perspective view of the antenna shown in Figure 1 with the front cover removed;

Figure 3 is a perspective view of the housing of the antenna shown in Figure 1 without the front cover;

Figure 4 is a cut-away view of a housing clip for holding the cover to the housing of the antenna shown in Figure 1;

Figure 5 is a front perspective view of an antenna dipole of the antenna, including two rectangular-shaped dipole elements, removed from the housing;

Figure 6 is a back perspective view of the antenna dipole of the antenna shown in Figure 5;

Figures 7-9 show three perspective views of one of the dipole members of the dipole shown in Figure 5 depicting the connection of an antenna cable;

Figure 10 is a perspective view of the other dipole member of the dipole shown in Figure 5;

Figure 11 is a cut-away, cross-sectional view of a punched-out clip used to hold an outer conductor of the antenna cable; and

Figure 12 is a cut-away, cross-sectional view of a portion of one of the dipole elements showing a punched-out connector for the inner conductor of the antenna cable.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0006] The following discussion of the preferred embodiments directed to a cost effective, indoor cellular band antenna is merely exemplary in nature, and is in no way intended to limit the invention or its applications or uses. Particularly, the antenna of the invention will be described as an antenna useful for an interior space, such as a hotel room or office building, and operable at cellular telephone frequencies. However, the particular design and features of the antenna of the invention has a wider application for other types of antenna usages, and other cellular bands such as PCS and GSM.

[0007] Figure 1 is a perspective view of a cellular band antenna 10, according to an embodiment of the present invention. The antenna 10 includes an outer metal housing 12 including a plastic cover or radome 14 that is transparent to the electromagnetic radiation of the wavelengths of interest. Figure 2 shows the same perspective view of the antenna 10 as in Figure 1, but with the radome 14 removed to expose an antenna dipole 16 within the housing 12. As will be discussed below, the antenna dipole 16 is a unique, cost effective antenna design that includes rectangular dipole elements for providing increased antenna performance, low cost, and ease of manufacture, as well as other advantages.

[0008] Figure 3 shows a perspective view of the housing 12 with the radome 14 and the antenna dipole 16 removed. The housing 12 includes opposing, trapezoidal-shaped top and bottom panels 18 and 20 and angled side panels 22 and 24 that extend from the radome 14 to a back panel 26, as shown. The combination of the side panels 22 and 24 and the back panel 26 define a 90E truncated corner configuration, in that if the back panel 26 was removed and the side panels 22 and 24 were extended, the side panels 22 and 24 would intersect at a 90E angle. The combination of the side panels 22 and 24, in combination with the top and bottom panels 18 and 20 and the back panel 26, reflect electromagnetic radiation towards the radome 14 to increase the antenna's front-to-back ratio (FBR).

[0009] A series of specially configured mounting slots 28 extend through the back panel 26 and the side panels 22 and 24 so that the antenna 10 can be readily and easily mounted at an inconspicuous location in the corner of a room by screws, or the like. Four "J-shaped" clips 30 are formed in the side walls 22 and 24 at each corner of the radome 14, so that the radome 14 can be mounted to the housing 12 by sliding it between the clips 30 and the top and bottom panels 18 and 20. A close-up view of one of the clips 30 is shown in Figure 4. A circular opening 34 is formed through the top panel 18 proximate the back panel 26 to allow a coaxial antenna cable 36 to extend into the housing 12 to be connected to the antenna dipole 16, as will be discussed in detail below. The housing 12 is formed by a cost effective metal rolling, cutting and/or punching process.

[0010] Figure 5 shows a front perspective view and Figure 6 shows a back perspective view of the antenna dipole 16 removed from the housing 12. The antenna dipole 16 includes a first dipole member 42 and a second dipole member 44. The dipole members 42 and 44 are mirror images of each other, except for minor differences apparent from the discussion and the figures. Figures 7-9 show different perspective views of the member 42 separated from the dipole 16 and connected to the cable 36. Figure 10 shows a perspective view of the dipole member 44 separated from the dipole 16. The dipole member 42 includes a rectangular dipole element 46, an elongated transmission balun member 52 and a mounting base plate 54. The dipole element 46, the transmission balun member 52 and the base plate 54 are formed of a single piece of a conductive metal, such as aluminum, that has been bent and formed to the shape as shown. A pair of bolts 56 extend through the base plate 54 to mount the dipole member 42 to the back panel 26 in an electrical contact.

[0011] The dipole member 44 includes substantially the same components as the dipole member 42 including a rectangular dipole element 58, a transmission balun member 59 and a base plate 61. The dipole elements 46 and 58 are monopole elements when separated. The two dipole elements 46 and 58 are positioned in substantially the same plane, and are directed towards the radome 14. The two extended parallel transmission members 52 and 59 of the dipole members 42 and 44 form a balun. The members 52 and 59 are spaced apart from each other by a predetermined distance based on the frequency band of interest to provide electromagnetic coupling between the dipole members 42 and 44 and an electrical feed to the elements 46 and 58, as would be understood to those skilled in the art. The spacing between and configuration of the dipole members 42 and 44, and the shape of the elements 46 and 58 allow the antenna 10 to operate at the bandwidth described herein with high performance.

[0012] The cable 36 is connected to the dipole member 42, and is the feed to transmit electromagnetic radiation to the antenna 10 and for electromagnetic radiation received by the antenna 10. The cable 36 includes an inner conductor 60 and an outer conductor 62. The outer conductor 62 is electrically connected to the dipole member 42 by a pair of mounting tabs 64 punched from the transmission balun member 52 and formed, as shown. Figure 11 shows a cut-away, cross-sectional view of one of the mounting tabs 64 without the outer conductor 62 mounted therein.

[0013] An insulating layer 66 between the inner conductor 60 and the outer conductor 62 extends through the balun member 52 and along its length between the balun members 52 and 59. A metal stand-off 68 formed from a cut-out section of the balun member 52 holds the inner conductor 62 and the insulating layer 66 of the cable 36 in place relative to the balun member 52. A foam spacer 67 is positioned between the balun member 52

and the inner conductor 62, as shown, to also hold the conductor 62 in the proper location. A metal stand-off 69 formed from a cut-off section of the balun member 59 also acts to provide appropriate spacing between the balun members 52 and 59. Additionally, a connecting strip 71, such as a Ty-Rap, can be wrapped around the balun member 52 to also provide dimensional integrity. The stand-off 68 and the spacer 67 are specially designed to position the inner conductor 60 at a desirable spacing between the balun member 52 of the dipole member 42 and the balun member 59 of the dipole member 44.

[0014] The inner conductor 60 extends back through the balun member 52 and is electrically connected to the rectangular dipole element 46 by a pair of connectors 70 formed by punching out a portion of the element 46 as shown. Figure 12 shows a cut-away cross-sectional view of one of the connectors 70.

[0015] The configuration and design of the antenna 10, as discussed above, provides a number of advantages for an antenna of this type in the prior art. Particularly, the antenna 10 is low cost, easy to manufacture, easy to assemble, simple to install, and provides superior electrical performance. The rectangular dipole elements 46 and 58 and the configuration of the antenna dipole members 42 and 44 provide high performance operation in the 800-1050MHz range. The antenna 10 has an excellent gain of 8.0 dBi or greater, and an excellent front-to-back ratio greater than 25 dB in the range of 780-960MHz and greater than 20 dB in the 960-1050MHz range. Additionally, the antenna 10 has a 3 dB beamwidth azimuth plane of 70E-80E and a 3 dB beamwidth elevation plane at 55E-70E. The impedance is 50 ohms, the polarization is linear, and the VSWR over the 800-1050 MHz range is less than 1.5 of the antenna 10.

[0016] In one embodiment, for the above-described performance, the antenna 10 has the following dimensions. The radome 14 is a square 9 inches by 9 inches. The back panel 26 is centered and has a width of 1.7 inches. The clips 30 are 0.26 inches long and have a spacing of 0.07 inches. The perpendicular distance from the radome 14 to the back panel 26 is 3.625 inches. The dipole elements 46 and 58 are 7.1 inches long, 2.962 inches wide and 0.062 inches thick. The balun members 52 and 59 are 3.585 inches long and 1.0 inches wide at their narrowest point. The base plate 54 is 1.50 inches square. The clips 64 and 70 and the stand-off 68 are all centered relative to the width of the dipole element 46 and the width of the balun member 52, and are 3.55 inches from the top and bottom of the dipole element 46. The stand-off 68 extends 0.21 inches from the balun member 52, and has a width of 0.2 inches. The clip 70 is about 0.37 inches long and provides an opening for the inner cable 60 of about 0.07 inches. The clip 62 provides an opening of 0.09 inches.

[0017] The foregoing discussion discloses and describes merely exemplary embodiments of the present

invention. One skilled in the art will readily recognize from such discussion, and from the accompanying drawings and claims, that various changes, modifications and variations can be made therein without departing from the spirit and scope of the invention as defined in the following claims.

Claims

1. An antenna system comprising:
 - a housing, said housing having at least one housing panel defining a reflector;
 - a dipole antenna positioned within the housing, said dipole antenna including a first dipole member and a second dipole member that are electro-magnetically coupled together, said first dipole member including a first rectangular-shaped dipole element and said second dipole member including a second rectangular-shaped dipole element, where the first and second dipole members are positioned on substantially the same plane; and
 - a cable extending into the housing and being electrically connected to one of the dipole members.
2. The system according to claim 1 wherein the first dipole member includes a first transmission balun member and a first mounting plate and the second dipole member includes a second transmission balun member and a second mounting plate, said first and second mounting plates being mounted to the housing, wherein the first and second transmission balun members are spaced apart a predetermined distance and are substantially parallel to each other, and wherein the first transmission balun member is substantially perpendicular to the first dipole element and the second transmission balun member is substantially perpendicular to the second dipole element.
3. The system according to claim 2 wherein the first dipole element, transmission balun member and mounting plate are formed of a single piece of metal, and the second dipole element, transmission balun member and mounting plate are formed of a single piece of formed metal.
4. The system according to claim 2 wherein the cable is mounted between the first and second transmission balun members.
5. The system according to claim 4 wherein the cable is mounted to the first dipole member.
6. The system according to claim 5 wherein an outer

conductor of the cable is electrically connected to the first transmission balun member and an inner conductor of the cable is electrically connected to the first dipole element.

7. The system according to claim 6 wherein the outer conductor of the cable is connected to the first transmission balun member by a punched-out section of the first transmission balun member and the inner conductor of the cable is connected to the first dipole element by a punched-out section of the first dipole element.
8. The system according to claim 5 wherein the cable is connected to the first transmission balun member by a stand-off so as to separate the cable from the first dipole member, said stand-off being formed from the first transmission balun member.
9. The system according to claim 1 wherein the housing includes first and second side panels that are angled relative to each other at about 90° and are connected to a rectangular-shaped back panel to form a truncated corner configuration.
10. The system according to claim 9 wherein the housing further includes trapezoidal-shaped top and bottom panels.
11. The system according to claim 1 wherein the housing further includes a front panel radome, said front panel radome being removably attached to side panels of the housing by extended clips.
12. The system according to claim 1 wherein the antenna system provides high performance reception and transmission in the 800 to 1050 MHz range.
13. An antenna for receiving and transmitting cellular-band frequencies, said antenna comprising:

a housing, said housing including angled side panels positioned at about 90° relative to each other, trapezoidal-shaped top and bottom panels, and a back panel defining a truncated corner configuration, said housing panels being an antenna reflector;

a first dipole member positioned within the housing, said first dipole member including a first dipole element, a first elongated transmission balun member connected to the first dipole element, and a first mounting plate connected to the first transmission balun member and the back panel, wherein the first transmission balun member is substantially perpendicular to the first dipole element;

a second dipole member positioned within the housing, said second dipole member including

a second dipole element, a second elongated transmission balun member connected to the second dipole element, and a second mounting plate connected to the second transmission balun member and the back panel, wherein the second transmission balun member is substantially perpendicular to the second dipole element; and

a coaxial cable extending through the housing, wherein an outer conductor of the cable is electrically connected to the first transmission balun member and an inner conductor of the cable is electrically connected to the first dipole element, said cable extending along the first balun member between the first and second balun members.

14. The antenna according to claim 13 wherein the first and second dipole elements are rectangular plates.
15. The antenna according to claim 14 wherein the first and second dipole elements are positioned on the same plane.
16. The antenna according to claim 13 wherein the first and second transmission balun members oppose each other and are substantially parallel.
17. The system according to claim 13 wherein the cable is connected to the first transmission balun member by a stand-off so as to separate the cable from the first dipole, said stand-off being formed from the first transmission balun member.
18. The system according to claim 13 wherein the outer conductor of the cable is connected to the first transmission balun member by a punched out section of the first transmission balun member and the inner conductor of the cable is connected to the first dipole element by a punched-out section of the first dipole element.
19. The system according to claim 13 wherein the housing further includes a front panel radome, said front panel radome being removably attached to side panels of the housing by extended clips.
20. A method of providing an antenna system, said method comprising the steps of:

providing a housing that includes at least one housing panel defining a reflector;
providing a dipole antenna having a first dipole member and a second dipole member where the first dipole member includes a first rectangular-shaped dipole element and said second dipole member includes a second rectangular-shaped dipole element;

mounting the first dipole member and the second dipole member within the housing so that the first and second rectangular-shaped dipole elements are on substantially the same plane and the first dipole member and the second dipole member are electro-magnetically coupled together; and
extending a cable into the housing and electrically connecting the cable to one of the dipole members.

21. The method according to claim 20 wherein the step of providing a dipole antenna includes forming the first dipole member from a single piece of metal to include the first dipole element, a first transmission balun member and a first mounting plate, and forming the second dipole member from a single piece of metal to include the second dipole element, a second transmission balun member and a second mounting plate, and wherein the step of mounting the dipole antenna within the housing includes electrically connecting the first and second mounting plates to the housing so that the first and second transmission balun members are parallel to each other and define a balun.
22. The method according to claim 20 wherein the step of providing a housing includes providing a housing having first and second side panels that are angled relative to each other at about 90° and are connected to a rectangular-shaped back panel to form a truncated corner configuration.
23. The method according to claim 20 wherein the step of connecting the cable to the first dipole member includes connecting an outer conductor of the cable to a first transmission balun member of the first dipole member and connecting an inner conductor of the cable to the first dipole element.




FIG. 1




FIG.2




FIG. 3




FIG. 4




FIG. 12









FIG. 11

















(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 102 349 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
17.03.2004 Bulletin 2004/12

(51) Int Cl.7: **H01Q 19/10**, H01Q 9/28,
H01Q 1/42, H01Q 1/24,
H01Q 1/00

(43) Date of publication A2:
23.05.2001 Bulletin 2001/21

(21) Application number: **00124374.0**

(22) Date of filing: **20.11.2000**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

- **Manassero, Greg A.**
San Jose, CA 95129 (US)
- **Belingeri, Ralph A.**
Woodside, CA 94062 (US)
- **Rucker, Donald L.**
Santa Cruz, CA 95060 (US)
- **Humphrey, Brent R.**
San Jose, CA 95139 (US)

(30) Priority: **22.11.1999 US 447166**

(71) Applicant: **Northrop Grumman Corporation**
Los Angeles, CA 90067-2199 (US)

(74) Representative: **Schmidt, Steffen J., Dipl.-Ing.**
Wuesthoff & Wuesthoff,
Patent- und Rechtsanwälte,
Schweigerstrasse 2
81541 München (DE)

(72) Inventors:
• **Jennetti, Anthony G.**
Sunnyvale, CA 94086 (US)
• **Serrano, Francisco J.**
Los Gatos, CA 95032 (US)

(54) High performance, directional cellular band antenna

(57) An indoor cellular band antenna (10) that is low cost, easy to assemble, easy to manufacture, and has better performance than those antennas existing in the art. The antenna (10) has an outer metal housing (12) including angled side panels (22, 24), trapezoidal-shaped top and bottom panels (18, 20) and a rectangular shaped back panel (26) defining a 90° truncated corner configuration. A radome (14) is positioned over the front of the housing (12) by sliding it beneath extending clips (30) formed to the side panels (22, 24). An antenna dipole (16) is mounted in the housing (12) and includes two dipole members (42, 44). Each dipole member (42, 44) includes a rectangular dipole element (46, 58), extended transmission balun members (52, 59) and a back mounting plate (54, 61) formed from a single piece of

metal. The transmission balun members (52, 59) are parallel to each other and specially spaced to provide a predetermined and electromagnetic coupling between the dipole members (42, 44). An antenna cable (36) extends through the top panel (18) of the housing (12). An outer conductor (62) of the cable (36) is electrically connected to one of the transmission balun member (52) of one dipole member (42) and an inner conductor (60) is electrically connected to the dipole element (46) of the same dipole member (42). The inner and outer conductors (60, 62) of the cable (36) are mounted to the dipole member (42) by connectors (64, 70) formed from the dipole member (42).

EP 1 102 349 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 12 4374

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 274 391 A (CONNOLLY KEVIN J) 28 December 1993 (1993-12-28) * column 3-5; figures 1-3 *	1,11,12, 20	H01Q19/10 H01Q9/28 H01Q1/42 H01Q1/24 H01Q1/00
Y		2-6, 13-16, 21,23	
Y		9,10,22	
Y	US 5 629 713 A (MAILANDT PETER ET AL) 13 May 1997 (1997-05-13) * figure 8A *	2-6, 13-16, 21,23	
A	US 5 724 051 A (HUYNH TAN D ET AL) 3 March 1998 (1998-03-03) * figures 5-7 *	2,3,21	
A	US 5 691 735 A (BUTLAND ROGER JOHN ET AL) 25 November 1997 (1997-11-25) * figure 3 *	2,21	
A	GB 2 191 045 A (GEN ELECTRIC CO PLC) 2 December 1987 (1987-12-02) * figure 3 *	2,4-6, 21,23	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H01Q
Y	US 3 750 185 A (EVANS G) 31 July 1973 (1973-07-31) * figure 2 *	9,10,22	
A		13-16	
A	US 5 625 365 A (DENNINGER VALENTINE L ET AL) 29 April 1997 (1997-04-29) * figure 1 *	11	
A	US 5 710 569 A (OH JUNG KUN ET AL) 20 January 1998 (1998-01-20) * figure 2A *	9,10, 13-16,22	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 8 January 2004	Examiner Ribbe, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02.92) (P4/C01)



European Patent
Office

Application Number
EP 00 12 4374

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

**LACK OF UNITY OF INVENTION
SHEET B**

Application Number
EP 00 12 4374

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-8, 20-21, 23

Mounting plates and balun details.

2. Claims: 9-10, 13-19, 22

Housing panels.

3. Claim : 11

Radome details.

4. Claim : 12

Operation frequencies.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 12 4374

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-01-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5274391	A	28-12-1993	NONE	
US 5629713	A	13-05-1997	NONE	
US 5724051	A	03-03-1998	EP WO	0870345 A1 9723019 A1
				14-10-1998 26-06-1997
US 5691735	A	25-11-1997	AU AU JP WO NZ	670130 B2 4986293 A 7509822 T 9403940 A1 255598 A
				04-07-1996 03-03-1994 26-10-1995 17-02-1994 25-06-1996
GB 2191045	A	02-12-1987	NONE	
US 3750185	A	31-07-1973	NONE	
US 5625365	A	29-04-1997	NONE	
US 5710569	A	20-01-1998	KR DE DE DK EP ES	185962 B1 69514206 D1 69514206 T2 730319 T3 0730319 A1 2141273 T3
				15-05-1999 03-02-2000 13-07-2000 19-06-2000 04-09-1996 16-03-2000

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82